

Part Number: 6542FE



Security & Sound, #22-3pr, BC, Shielded, CMP

# **Product Description**

Security & Sound Cable, Plenum-CMP, 3-22 AWG stranded bare copper pairs with Flamarrest® insulation, Beldfoil® shield and Flamarrest® jacket with ripcord

# **Technical Specifications**

### **Product Overview**

Suitable Applications: Security Systems, Intercom/PA Systems, Sound/Audio Systems, Power Limited Controls		
Physical Characteristics (Overall)		
Conductor		

AWG	Stranding	Material	No. of Pairs
22	7x30	BC - Bare Copper	3
Condu	uctor Count:		6
Condu	uctor Size:		22 AV

### Insulation

Material	Material Trade Name	Nominal Wall Thickness
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.009 in

# **Color Chart**

Number	Color
1	Black & Red
2	Black & White
3	Black & Green

### **Outer Shield Material**

Тур	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Тар	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	24	Solid

# **Outer Jacket Material**

Material	Material Trade Name	Nominal Diameter	Nominal Wall Thickness	Ripcord
LS PVC - Low Smoke Polyvinyl Chloride	Flamarrest®	0.216 in	0.015 in	Yes

# **Electrical Characteristics**

# Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
16.3 Ohm/1000ft	13.9 Ohm/1000ft

### Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
33 pF/ft	59.4 pF/ft
Shielding:	Foil(s) or Copper Tape(s)

### Inductance

Nominal Inductance 0.18 µH/ft

### Current



### Voltage



### **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	0°C To +75°C

### **Mechanical Characteristics**

Bulk Cable Weight:	26.1 lbs/1000ft
Max Recommended Pulling Tension:	60.1 lbs
Min Bend Radius/Minor Axis:	2.25 in

### **Standards**

NEC Articles:	800
NEC/(UL) Specification:	CMP
CEC/C(UL) Specification:	CMP

### **Applicable Environmental and Other Programs**

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-04-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT6
UL Flammability:	NFPA 262 Plenum Flame Test (UL910)
UL voltage rating:	300 V RMS

# Plenum/Non-Plenum

Plenum (Y/N):	Yes

# **Part Number**

Non-Plenum Number: 5542FE
---------------------------

### Variants

Item #	Color
6542FE 8771000	Natural
6542FE 877U1000	Natural

## © 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.