



Technical specification:

Rated voltage: IEC 60664-1	100 V
Current rating: IEC 60512-3	total ampacity: 3 contacts 10 A 16 contacts 8 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-40°C ... +125°C
Mating cycles: IEC 60512-9a	>=100
Wire cross section at contact Ø1,0 mm: contact Ø1,5 mm:	AWG20/ max. 0,5 mm ² AWG17/ max. 1,0 mm ²
Contact termination:	Solder cup

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PA6, PBT, UL 94
Cable sealing:	NBR
Sealing:	FPM
Coupling nut:	GD-Zn, nickel plated
Housing:	GD-Zn, nickel plated

Part no:	Description:	Cable sealing:
41-90001	SAL - 23 - RKC16+3 - L	For external cable diameter 3 - 7 mm, 7 - 12 mm, 11 - 17mm

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	 dim. in mm		title: Female connector M23, 16+3pos, field attachable, axial, with solder cup		
		date		name	
	tolerance of cable:	drawn	12.10.11	Franz	dwg no: 41K1A442
	general tolerance: 0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm	appd.	12.10.11	Mankopf	
			part no: see table		
<small>THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH</small>					