	1		2		3		4		5		\Box
	2.54			 	4.57 9.14 9.14 9.14 9.14 9.14		NENT VIEW	MATERIAL INSULATOR M FLAMMABILIT COLOR: BLAC CONTACT MA CONTACT TYI CONTACT TYI SHIELDING: E QUALITY CLA ENVIRONMEN OPERATING T COMPLIANCE ELECTRICAL CURRENT RA WORKING VC INSULATION F WITHSTANDIN CONTACT RE STANDARD	CHARACTERISTICS MATERIAL: PBT Y RATING: UL94-V0 CK TERIAL: COPPER ALLOY PE: STAMPED ATING: GOLD RONZE NI PLATED SS: 500 MATING CYCLES NTAL TEMPERATURE: -40 °C UP TO 85 ° CUP		В
	OHS Compliant		┿╥┧	D 5.84 9.14 11.43 15.49	4.57 10.89	X7=8.89					С
G F E D						TOLERANCE X = ⁺ /_ 0.2 X = ⁺ /_ 0.15					
C B A	17-JAN-14 03-JAN-14 03-FEB-07	DRAWING UL & TEMP UPDATE PDF	AK QL CH	APPROVAL: RJ	UNIT: MM SCALE: SHEET: 1/2	2		AR JACK TAB UP AN	AL STACKED PORT 8P8C ID TAB DOWN	SIZE	D
REV	DATE	FILE	BY	1	DRAW:		1				

1	2	3	4	5	-
					_

А

В

С

Cautions and Warnings:

This electronic component is designed and developed with the intention for use

in general electronics equipments.

Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc. where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body, Wurth Elektronik must be asked for a written approval.

In addition, even electronic component in general electronic equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before by the user before usage.

R	oHS Compliant							
G				PROJECTION:	GENERAL TOLERANCE]
F					.X = ⁺ /_ 0.2			
E					.XX = ⁺ /_ 0.15			
D						WÜRTH ELEKTRONĬK		
С				APPROVAL: JC	UNIT: MM	DESCRIPTION: DISCLAIMER	SIZE	lD
В]	SCALE:			٢
A	10-SEP-14	PDF	QL	1	SHEET: 2/2	WERI PART NO: DISCLAIMER	A4	
REV	DATE	FILE	BY		DRAW: QL			